Kolibri 2 Rail NIST O2 Standard



Manufacturer:	Greggersen
Product Number:	906420

Description

KOLIBRI 2, O2, 0...15 l/min

- Standard RAIL-MOUNTED UNIT -

Flow Settings:

0 / 0.5 / 1 / 1.5 / 2 / 3 / 4 / 6 / 8 / 12 / 15 l/min

Compact Flowmeter KOLIBRI 2

with fixed orifices and selector mechanism

Medical compact flowmeter for mounting on a 25x10mm equipment rail; gas inlet NIST integrated into the rail clamp; with handwheel - stepwise adjustable flow rate, outlet 9/16-18 UNF thread

Ergonomically optimised adjustment device and readability of the selected flow setting from various viewing directions

© 2026, Greggersen Gasetechnik GmbH

and angles.

Frontal operating concept -> greater safety when
setting the correct flow rate

Gas Type: Oxygen / O2
Connection: NIST in accordance with DIN EN ISO 18082
Outlet: 9/16-18 UNF
Flow Rate: 0...15 l/min at inlet pressure 450 kPa (4.5 bar)

Accessories required for operation:
900619 - Hose connection 9/16-18 UNF

Properties

Gas Type	O2-Oxygen
Inlet Standard	NIST
Variant	Standard

© 2026, Greggersen Gasetechnik GmbH