Kolibri 2 Rail CH NIST O2 Standard



Manufacturer:	Greggersen
Product Number:	906445

Description

KOLIBRI 2, O2, 0...15 l/min

- Standard CH RAIL-MOUNTED UNIT -

Flow Settings:

0 / 0.5 / 1 / 1.5 / 2 / 3 / 4 / 6 / 8 / 12 / 15 l/min

Compact Flowmeter KOLIBRI 2

with permanently attached orifices with selection device

Medical compact flowmeter for mounting on an

equipment rail; gas inlet NIST integrated in the rail clamp;

with handwheel - incrementally adjustable flow rate, outlet 9/16-18 UNF thread

-> With special, spring-loaded

rail clamp for up to 50mm rails <-

© 2026, Greggersen Gasetechnik GmbH

Adjustment device ergonomically optimised and readability of the set flow setting possible from various viewing directions and angles.

Frontal operating concept -> increased safety when setting the correct flow rate

Gas Type: Oxygen / O2
Connection: NIST according to DIN EN ISO 18082
Outlet: 9/16-18 UNF
Flow Rate: 0...15 l/min at inlet pressure 450 kPa (4.5 bar)

Accessories required for operation:
900619 - Hose connection 9/16-18 UNF

Properties

Gas Type	O2-Oxygen
Inlet Standard	CH NIST
Variant	Standard

© 2026, Greggersen Gasetechnik GmbH