Kolibri 2 Rail NIST CO2 Standard



Manufacturer:	Greggersen
Product Number:	906435

Description

KOLIBRI 2, CO2, 0...15 l/min

- Standard RAIL-MOUNTED UNIT -

Flow Settings:

0 / 0.5 / 1 / 1.5 / 2 / 3 / 4 / 6 / 8 / 12 / 15 l/min

Compact Flowmeter KOLIBRI 2

with permanently attached orifices with selector mechanism

Medical compact flowmeter for mounting on an

equipment rail 25x10mm; gas inlet NIST integrated into

the rail clamp; with handwheel - step-adjustable

flow rate, outlet 9/16-18 UNF thread

Ergonomically optimised adjustment mechanism and readability

of the set flow setting from various viewing directions

© 2026, Greggersen Gasetechnik GmbH

and angles possible.

Front-facing operating concept -> increased safety when setting the correct flow rate

Gas type: Carbon dioxide / CO2
Connection: NIST in accordance with DIN EN ISO 18082
Outlet: 9/16-18 UNF
Flow rate: 0...15 l/min at inlet pressure 450 kPa (4.5 bar)

Accessories required for operation:
900619 - Hose connection 9/16-18 UNF

Properties

Gas Type	CO2-Carbon Dioxide
Inlet Standard	NIST
Variant	Standard

© 2026, Greggersen Gasetechnik GmbH